

NTIRE 2025 Challenge on Efficient Burst HDR and Restoration: Datasets, Methods, and Results

Sangmin Lee* Eunpil Park* Angel Canelo* Hyunhee Park* Youngjo Kim*
 Hyung-Ju Chun* Xin Jin* Chongyi Li* Chun-Le Guo* Radu Timofte*
 Qi Wu Tianheng Qiu Yuchun Dong Shenglin Ding Guanghua Pan Weiyu Zhou
 Tao Hu Yixu Feng Duwei Dai Yu Cao Peng Wu Wei Dong Yanning Zhang
 Qingsen Yan Simon J. Larsen Ruixuan Jiang Senyan Xu Xingbo Wang Xin Lu
 Marcos V. Conde Javier Abad-Hernández Álvaro García-Lara Daniel Feijoo
 Álvaro García Zeyu Xiao Zhuoyuan Li

Abstract

This paper reviews the NTIRE 2025 Efficient Burst HDR and Restoration Challenge, which aims to advance efficient multi-frame high dynamic range (HDR) and restoration techniques. The challenge is based on a novel RAW multi-frame fusion dataset, comprising nine noisy and misaligned RAW frames with various exposure levels per scene. Participants were tasked with developing solutions capable of effectively fusing these frames while adhering to strict efficiency constraints: fewer than 30 million model parameters and a computational budget under 4.0 trillion FLOPs. A total of 217 participants registered, with six teams finally submitting valid solutions. The top-performing approach achieved a PSNR of 43.22 dB, showcasing the potential of novel methods in this domain. This paper provides a comprehensive overview of the challenge, compares the proposed solutions, and serves as a valuable reference for researchers and practitioners in efficient burst HDR and restoration.

1. Introduction

Raw image fusion is a crucial task in image signal processing with widespread real-world applications. Due to missing values in the Bayer inputs and their specific form, it requires slightly different handling techniques and is considered a challenging task. Multi-frame fusion is designed

to obtain high-quality images by using multiple images with consecutive time series, as is the case with RAW burst denoising [20, 21, 26, 28, 43, 63, 64, 73, 92] or RAW image super-resolution [19, 21, 37, 89, 91]. Specifically, in the last decade, there have been rapid developments in deep learning techniques for image processing to tackle increasingly difficult problems, such as denoising [1, 6, 20, 27, 47, 51, 99, 104, 105], deblurring [12, 62, 65, 80, 100, 103], super-resolution (SR) [3, 40, 48, 50, 54, 106, 107], and high dynamic range (HDR) reconstruction [8, 22, 39, 41, 57, 64, 68, 113]).

Specifically, multi-exposure images contain richer information, and various methods have been proposed to restore clean images from degraded multi-frame inputs. Over the past decade, researchers have increasingly explored multi-exposure image fusion using noisy, blurry, misaligned frames with varying exposure levels [26, 28, 30, 39, 110]. Furthermore, a previous New Trends in Image Restoration and Enhancement (NTIRE) challenge [111] focused on the restoration and enhancement of low-light RAW images from burst and dual-exposure inputs, leading to several novel approaches and insights [7, 18, 52, 93, 94]. These advancements suggest that, despite their inherent challenges, multi-image processing methods can offer significant advantages in addressing such problems and achieving more accurate results.

Inspired by previous works, we proposed a novel challenge in NTIRE 2025 to restore an RGB image by fusing multiple degraded RAW frames. In particular, compared to previous challenges, we introduced a more difficult task by incorporating a mixed noise distribution (Gaussian and Poisson), increasing the number of input frames, and applying several challenging degradation processes. This multi-frame fusion task has not been covered in previous NTIRE challenges, and it is expected to significantly contribute to

*S. Lee, E. Park, H. Park, H. Chun, Y. Kin, A. Canelo, C. Li, C. Guo, X. Jin and R. Timofte are the NTIRE 2025 challenge organizers, while the other authors are participants in this challenge. Each team described their own method in the report. Appendix A contains the authors' teams and affiliations.

NTIRE 2025 webpage: <https://cvlai.net/ntire/2025>.

Code: <https://github.com/Eve-ctr/RawFusion>.

advancements in this field. Furthermore, another key objective of this challenge is to encourage participants to develop highly efficient network architectures suitable for on-device deployment, enabling real-world applications.

Overall, this paper presents the NTIRE 2025 Challenge on *Efficient Burst HDR and Restoration*, which aims to explore efficient multi-frame fusion solutions from a novel perspective. Participants were tasked with designing an appropriate image signal processing (ISP) module to synthesize clean, aligned HDR RGB images from nine misaligned, noisy, and degraded RAW inputs. In the final testing phase, six teams successfully submitted valid solutions. This paper provides an overview of their methods and reports their performance. The proposed approaches highlight potential new state-of-the-art benchmarks in efficient multi-frame HDR fusion and restoration, which are expected to not only accelerate research in this field but also drive real-world industrial applications.

This challenge is one of the NTIRE 2025¹ Workshop associated challenges on: ambient lighting normalization [82], reflection removal in the wild [95], shadow removal [81], event-based image deblurring [77], image denoising [78], XGC quality assessment [55], UGC video enhancement [75], night photography rendering [23], image super-resolution (x4) [10], real-world face restoration [11], efficient super-resolution [72], HR depth estimation [97], efficient burst HDR and restoration [42], cross-domain few-shot object detection [25], short-form UGC video quality assessment and enhancement [45, 46], text to image generation model quality assessment [29], day and night raindrop removal for dual-focused images [44], video quality assessment for video conferencing [34], low light image enhancement [56], light field super-resolution [87], restore any image model (RAIM) in the wild [49], raw restoration and super-resolution [14], and raw reconstruction from RGB on smartphones [15].

2. NTIRE 2025 Efficient Burst HDR and Restoration Challenge

2.1. Overview

The goal of this competition is to develop an efficient algorithm for burst HDR and restoration. More precisely, the task involves generating HDR images from multiple consecutive RAW frames captured at different exposure times. This requires aligning and denoising RAW frames taken over a period of time, each with varying exposure settings (and consequently different noise levels), and then efficiently fusing them. This challenge simulates real-world mobile photography scenarios using devices such as smartphones or DSLR cameras. The primary objective is to inspire innovations in mobile and camera applications by

encouraging the development of efficient on-device image signal processing (ISP) models. A simple baseline code and model are provided for participants as a starting kit (<https://github.com/Eve-ctr/RawFusion>).

Specifically, this competition requires solving the following three key tasks:

1. **Multi-frame RAW image fusion:** The inputs consist of consecutive multi-frame RAW Bayer images.
2. **HDR image synthesis:** The inputs exhibit varying brightness levels, leading to color saturation. The goal is to fuse these frames into a single High Dynamic Range (HDR) image.
3. **Restoration:** The inputs contain various levels of noise, and the objective is to restore a clean ground truth (GT) image.

Overall, designing an efficient algorithm for both multi-frame fusion and restoration remains a challenging task. The ultimate goal of this competition is to develop an approach suitable for on-device deployment, enabling real-world applications on mobile devices.

2.2. Datasets

Instead of using existing multi-frame RAW fusion datasets such as BurstSR [3, 21, 37, 61], SyntheticBurst [5, 20, 37, 89], LLFF-N [67, 79], or other datasets from previous NTIRE challenges [2, 4, 111], we introduce a novel synthetic RAW HDR fusion dataset in this competition to encourage innovative approaches.

Specifically, the training dataset is generated using a virtual imaging pipeline. For each scene, nine clean RAW frames with various exposure levels are captured, and the corresponding ground-truth (GT) HDR RGB image is synthesized from these frames. The provided RAW frames have three different exposure levels (low, medium, and high), resulting in three distinct noise levels. To simulate real-world burst RAW acquisition, the dataset incorporates various degradations, including noise, rotation, translation, and motion blur.

The first frame in each sequence serves as the *reference frame*, which is perfectly aligned with the ground-truth image. Figure 1 illustrates an example composition of a scene in the dataset. The core objective of this dataset is to encourage participants to explore *how to effectively utilize the information from multiple input frames while considering the unique characteristics of each frame*.

The training, validation, and test datasets are constructed using the same methodology, with all images having a resolution of $768(H) \times 1536(W)$, as depicted in Figure 1(a). The training set consists of 300 scenes, each containing nine RAW input frames and one ground-truth RGB image. The validation and test sets each contain 20 scenes, with the GT images in these sets hidden from participants.

¹<https://www.cvlai.net/ntire/2025/>




Figure 1. Visualization of the dataset proposed in this competition. (a) Example of an HDR RGB GT image. (b) Cropped patch of (a). (c) Nine input RAW frames corresponding to (b), captured at three different exposure levels. Participants are required to fuse these noisy, misaligned and degraded frames to reconstruct the ground-truth RGB image in (b).

2.3. Challenge Rules

2.3.1. Metric

The evaluation is based on the comparison between the generated images and the corresponding ground-truth images. Following previous NTIRE challenges [4, 9, 47, 84–86, 109, 111], we use the average Peak Signal-to-Noise Ratio (PSNR) [32] across the full test set to determine the final ranking. Although the dataset is provided in 16-bit `.tif` format, PSNR is measured after conversion to 8-bit format. As an additional reference, we also provide the Structural Similarity Index Measure (SSIM) [88], computed in grayscale, to participants.

2.3.2. Restrictions on Model Parameters and FLOPs

Since this competition emphasizes the development of efficient on-device models, there are strict constraints on computational cost and memory. Specifically, submitted models must not exceed 30M parameters and 4T Floating point Operations (FLOPs) when generating a full-sized output RGB image of size $1 \times 3 \times 768 \times 1536$. The FLOP count is measured using the `FlopCountAnalysis` function from the `fvcore` module, as adopted in prior works [71, 98].

2.3.3. Others

Participants are allowed to employ any training techniques as long as they adhere to the constraints outlined in Section 2.3.2. For instance, they may utilize external public datasets for pre-training, incorporate pre-trained networks, or leverage generative models/transformers, etc. Furthermore, there are no further constraints on memory usage or inference time. Lastly, the use of all input frames is not mandatory. To optimize computational efficiency and reduce FLOPs, participants may selectively use a subset of frames before applying fusion techniques.

Team name	PSNR \uparrow	SSIM \uparrow	Params (M)	FLOPs (T)	Time (s)
InvisionAI	43.22	0.992	29.051	3.965	7.12
DeepTrans	42.75	0.991	12.839	3.864	0.24
SimonLarsen	41.38	0.989	18.651	1.685	0.74
E_Group	40.64	0.988	8.386	0.288	0.62
CidautAI	37.51	0.979	3.346	0.279	0.064
X-L	33.85	0.934	1.73	0.346	0.088

Table 1. The final results of participants. Team InvisionAI achieved the highest PSNR value of 43.22 dB using maximal resources close to the competition restriction. The inference time represented in the rightmost column is measured by a single NVIDIA H100 GPU.

2.4. Challenge Phases

(1) *Training and validation phase*: Participants are provided with 300 training scene pairs and 20 validation inputs from our constructed dataset. The training phase lasts for three weeks, during which participants can submit their validation results to receive PSNR feedback. The GT images for the validation set remain hidden from participants. Instead, they can submit their enhanced results to the evaluation server, which computes PSNR and SSIM scores for the generated images and provides immediate feedback. The resulting PSNR values are displayed on the leaderboard, visible for all participants.

(2) *Testing phase*: The test phase lasts for one week, during which participants can submit their final results. They are given access to the testset consisting of 20 scenes, with GT images remaining undisclosed. Similar to the validation phase, PSNR scores for test results are displayed on the leaderboard. Participants are required to submit their enhanced outputs to the Codalab evaluation server, along with an email to the organizers containing their code and a factsheet. The organizers verify and execute the provided code to verify the final results.

3. Challenge Results

The competition had a total of 217 participants, with six teams ultimately submitting their final results. Their quantitative performance is summarized in Table 1, while Figure 2 visualizes qualitative results for several scenes from the test set.

Team InvisionAI won the competition, achieving the highest PSNR value of 43.22 dB on the test set, outperforming the second-place team by 0.47 dB. Their model was designed to fully utilize the competition’s constraints (30M model parameters and 4.0T FLOPs, as described in Section 2.3.2) to maximize performance. Additionally, their model also achieved the highest SSIM score of 0.992, slightly surpassing the second-place result.

From an efficiency perspective, inference time for each model was measured under the same conditions using a sin-



Figure 2. The visualization of the participants’ final results, along with the corresponding input reference frames and GT images. The first row displays the full input scenes, while the subsequent rows show cropped patches from the images. Each column represents the GT image, the input reference frame, and the results produced by the participants’ models. Higher-performing models generate outputs that closely restore the GT, whereas the last two rows (e, f) illustrate cases where complete restoration was unsuccessful.

gle NVIDIA H100 GPU. The time required to restore a full-size (768×1536) image was averaged and is reported in Table 1. Team ImvisionAI’s winning model had the longest inference time at approximately 7 seconds, whereas team CidautAI achieved the fastest processing time at 64 ms per image. Given the trade-off between speed and performance, selecting an appropriate model depends on the specific application requirements.

Notably, an alternative approach to efficiency evaluation involves using a PSNR/time metric, as seen in other challenges [16, 33]. If the competition had adopted this metric, the rankings and model designs might have differed. For instance, Team ImvisionAI’s slow inference speed is not due

to GPU computation but rather an architectural bottleneck, which could be further optimized. It is important to note that this competition did not impose running time or memory usage constraints beyond those defined in Section 2.3.2; instead, the primary focus was on achieving the best performance within the given resource limits.

To compare the qualitative performance of the participants’ models, we selected six representative test scenes that highlight key characteristics of their results. These selected scenes are displayed in the first row of Figure 2, with cropped patches zoomed in for detailed inspection.

In Figure 2(a), all participants successfully restored textures in the bright regions of the scene. However, artifacts




Figure 3. The model proposed by the team ImvissionAI, named recursive multi-exposure alignment with spatiotemporal decoupling. They designed two stages of training the models, with each stage focusing on learning multi-frame alignment and image restoration, respectively. After the alignment module has been trained, it is frozen during the training of the restoration model in the second stage.

start to appear in the synthesized images, such as the vertical line in the rightmost column of Figure 2(b) or the noisy outputs in the right two columns of (c). This issue becomes even more evident in the restoration of letters in dark areas, as shown in (d), where only the top three teams produced clearly recognizable results.

Figures 2(e) and (f) illustrate two of the most challenging cases in the test set. In (e), faint horizontal lines in the GT image were not fully restored, while in (f), the details of trees in dark areas were not completely reconstructed. More specifically, the bright forest regions in (f) were slightly better restored by team ImvissionAI compared to team DeepTrans, whereas both struggled to recover details in the dark regions. Restoring dark areas is particularly difficult because the original signal is only partially available from overexposed frames. Considering the extreme noise levels in the input frames, as displayed in the second column of the figure, these cases exemplify the inherent challenges of this competition.

Finally, we analyze the results in relation to model complexity. Notably, the second-place team DeepTrans, achieved visually comparable results while using less than half the number of parameters compared to team ImvissionAI. Although some differences in fine details were observed, their approach demonstrates an effective balance between performance and efficiency, making it a strong can-

didate for real-world applications where time and memory constraints are critical, such as on-device environment.

4. Challenge Methods

4.1. ImvissionAI

General method description. The team proposed an recursive multi-exposure alignment with spatiotemporal decoupling for efficient burst hdr and restoration named RASD [69]. Burst HDR and Restoration from RAW to RGB, aiming for an end-to-end solution, is a challenging task due to two key contradictions: (1) the information differences caused by brightness, noise, saturation, and dead-black regions across multi-exposure data domains, and (2) the disparity between alignment and restoration in the temporal and spatial domains. Neglecting these factors would lead to inefficient joint optimization.

To address these challenges, the team propose a framework that explicitly considers these contradictions at both the alignment and restoration stages. Specifically, as illustrated in Fig. 3, for alignment, the team leverage statistically derived luminance priors for truncation-free exposure alignment toward the longest exposure to prevent alignment errors caused by too many saturated pixels and introduce a recursive *Flow-based Enhanced Deformable Alignment* (F-EDA) module to achieve multi-exposure spatial alignment. Specifically, since spynet [70] is trained in the non-




Figure 4. The proposed model by DeepTrans, named flow-guided deformable alignment with channel-wise self-attention reconstruction.

linear RGB domain, the team use a learnable feature mapping to transform the input into a domain with a smaller gap, reducing flow errors and enabling more accurate optical flow estimation by spynet [70]. These ensure more stable and accurate alignment across different exposure levels. Additionally, to balance the trade-off between alignment and restoration, the team adopt a two-stage training strategy that decouples spatiotemporal learning, in the align stage (stage 1), the team use a few Restormer [101] blocks to maximize alignment. In the restoration stage (stage 2), the team use the full Restormer architecture to maximize the overall restoration, addressing blurring, noise, and providing a RAW to sRGB mapping. Additionally, they found that decomposing the Bayer pattern channels during the restoration phase significantly reduced accuracy. Therefore, they kept the original RAW pattern format. They analyzed that the decomposition operation lost the spatial relationships between different color channels, which lowered the restoration accuracy.

Implementation details. The team used AdamW optimizer ($\alpha = 0.9$ and $\beta = 0.9$) with 1000 training epochs each for stage 1 and stage 2. The initial value of the learning rate was 8×10^{-4} and was updated with cosine annealing schedule. The patch size was set to 128×128 pixels. For data augmentation, they only used bayeraug [53] for random flips and transposition. In the testing phase, the team used TLC [13] for full image inference, and note that the addition of TLC brings no complexity gain.

4.2. DeepTrans

General method description. The overall architecture of their model is illustrated in Figure 4. They first adopt an Optical Flow Alignment Block (OFAB) to align the nine input RAW frames. This module comprises convolutional layers for shallow feature extraction and integrates a pre-trained SpyNet [70] for the optical flow estimation. As the

original model is designed for four-channel RAW inputs, and the input data consists of single-channel RAW images, they convert them into a four-channel format according to the RGGGB Bayer pattern. This conversion reduces the spatial resolution of each frame by half.

After alignment, the nine converted frames are concatenated and passed through a transposed convolution layer to restore the original spatial resolution. This operation enables effective aggregation and utilization of complementary information from the multiple input frames.

The fused features are then fed into a four-level symmetric encoder-decoder architecture to extract deep representations. Each level of the encoder-decoder consists of multiple transformer blocks. The encoder progressively down-samples the spatial dimensions while increasing the feature dimensionality, and the decoder correspondingly upsamples the low-resolution latent features to reconstruct high-resolution representations. To facilitate the reconstruction process, skip connections are introduced to concatenate encoder features with corresponding decoder features at each level.

A convolutional layer is subsequently applied to the refined features to predict the residual image. Finally, a transposed convolution layer [102] is employed to generate an aligned reference frame with the same number of channels as the residual. The restored image is obtained by adding the residual to this reference frame.

Implementation details. During the training process, images are randomly cropped to patches with a size of 128×128 , and are subject to random flipping and rotation. They used the PyTorch framework and adopted the Adam optimizer with $\beta_1 = 0.9$ and $\beta_2 = 0.999$. The initial learning rate was set to 2×10^{-4} , using CosineAnnealingLR [59] that gradually reduces to 2×10^{-6} over 80 epochs. The model was trained on 8 RTX 4090 GPUs for a total of 80 epochs, amounting to 1 day of training.




Figure 5. The model proposed by Team SimonLarsen. The full three-stage model architecture is shown in the top, the basic CN block on the right and the CNRDB block in the bottom. dw in the CN block denotes depth-wise convolution.

4.3. SimonLarsen

General method description. Team SimonLarsen proposed the FlowCNRDB model shown in Figure 5. They aimed to build a modern fusion and restoration model without self-attention by instead applying the design principles outlined in ConvNeXt [58] and ConvNeXt V2 [90] to produce an efficient and fully-convolutional model. The overall network architecture consists of three stages: feature extraction, frame alignment, and finally a joint fusion and restoration model. In the first and second stages, each frame is processed in parallel, while the last stage processes all frames together to produce the final output.

All stages of the model utilized the basic block design of ConvNeXt V2 employing large kernel depth-wise convolutions followed by a point-wise MLP and Global Response Normalization (GRN). To avoid overfitting, dropout is used throughout the model. The global feature aggregation in GRN will lead to train-test time inconsistency when trained on patched inputs. To mitigate this issue, a local aggregation method similar to test-time local conversion [13] was used during inference.

The **feature extraction stage** encodes each frame $\mathbf{I}_i \in \mathbb{R}^{H \times W \times 1}$ into a latent representation $\mathbf{Z}_i \in \mathbb{R}^{\frac{H}{2} \times \frac{W}{2} \times C}$. The input frames are first patched using a 2×2 convolution with stride 2. The patch size was chosen to match the GRBG filter size of the raw Bayer inputs. Deep features are then extracted through a series of ConvNeXt (CN) blocks.

The **frame alignment** model is a U-Net architecture [74] consisting of CN blocks. Given an encoded reference and target frame $(\mathbf{Z}_{\text{ref}}, \mathbf{Z}_i) \in \mathbb{R}^{\frac{H}{2} \times \frac{W}{2} \times 2C}$ (concatenated on the channel axis), the model outputs a dense flow field $\mathbf{F}_i \in \mathbb{R}^{\frac{H}{2} \times \frac{W}{2} \times 2}$ estimating the displacement between the reference and the target.

The predicted flow field is used to warp the target frame

to match the reference frame using bilinear grid sampling. Tokens outside the target frame are padded with zeros, and a padding mask is computed to be used in the fusion stage.

The **fusion and restoration** stage takes in the full set of aligned frames and padding masks, concatenated on the channel axis, and predicts the final RGB output image $\hat{\mathbf{Y}} \in \mathbb{R}^{H \times W \times 3}$. During training, frames are randomly shuffled within the three exposure time groups to effectively prevent the model from associating specific channels with the reference frame. This step is necessary to force the model to utilize all frames and, as a result, learn how to align the frames in the second stage.

The fusion stage consists of a series of ConvNeXt Residual Dense Blocks (CNRDB) using a macro design similar to DRCT [31], but replacing Swin transformer layers with CN blocks. In addition, a linear layer was used to project the number of channels down to a common size before each CN block to constrain the number of parameters. The output from the fusion stage is unpatched with a 2×2 pixel shuffle operation followed by a 3×3 convolution down to 3 channels to produce the final output image.

Training details. The model was trained solely on the provided training dataset with the last 20 scenes reserved for validation. For data augmentation, Bayer-preserving [53] horizontal/vertical flipping, rotation (in 90 degree increments) and random cropping was used. The model was trained solely with MSE loss. No additional losses were used to supervise the frame alignment.

The model was trained at 256×256 resolution with batch size 10 for 224k iterations on a single NVIDIA RTX A6000 GPU using automatic mixed precision. The initial learning rate was set at 3×10^{-4} and gradually reduced to 10^{-7} using a cosine annealing schedule. Throughout training, the AdamW optimizer was used with weight decay = 0.01, $\beta_1 = 0.9$, and $\beta_2 = 0.999$.




Figure 6. The proposed model by team E_Group.

4.4. E_Group

General method description. Team E_Group proposed a model that utilizes the SFHFormer [35] block, which consists of a hierarchical encoder-decoder structure composed of five stages. The structure includes a two-scale encoder (stage-1 and stage-2), a bottleneck (stage-3), and a two-scale decoder (stage-4 and stage-5). The core components of the SFHFormer block are: (a) Local Global Perception Mixer (LGPM) and (b) Multi-kernel ConvFFN (MCFN). The LGPM is designed to capture both local and global feature representations, while the MCFN enhances the feature transformation capabilities through multiple kernel convolutions.

Training strategy. Team E_Group employs the AdamW optimizer with $\beta_1 = 0.9$ and $\beta_2 = 0.999$ to train the SFHFormer model. The initial learning rate was set to 7.5×10^{-4} , and a cosine annealing strategy [59] was adopted to gradually decrease the learning rate from the initial value to 5×10^{-6} . This learning rate scheduler is crucial for fine-tuning, as it enables smooth convergence and helps the model escape local minima by periodically restarting the annealing process.

In addition to the optimizer settings, Team E_Group’s training process integrated mixup data augmentation with a mixup parameter $\beta = 1.2$ and identity mapping enabled. This augmentation strategy enhances data diversity, leading to improved model robustness by interpolating between training samples.

Furthermore, Team E_Group’s framework utilized the FFT loss (fftLoss) for pixel-level optimization. The FFT loss, with a weight of 1.0 and mean reduction, operates in the frequency domain to capture high-frequency details,

thereby improving the recovery of fine textures and edges in the restored images. This approach mitigates the blurring issues commonly associated with direct pixel-wise losses such as L1 or L2.

Team E_Group also incorporated pre-trained weights into the training pipeline. By initializing the model with weights obtained from previous training stages, the fine-tuning process was accelerated and the model benefits from the learned feature representations, ensuring better performance in the restoration task.

All experiments were conducted using PyTorch 1.11.0 on a system equipped with two NVIDIA 4090 GPUs. The batch size was set to 2 and a crop size of 256 is used, which were optimized for both memory efficiency and effective training on high-resolution image data. This comprehensive training strategy, combining advanced optimizer settings, dynamic learning rate scheduling, effective data augmentation, and frequency-domain loss computation, ensures that the SFHFormer model achieves a balanced performance in both global structure recovery and local detail enhancement.

4.5. CidautAI

General method description. The challenge involves handling sequences of raw images with varying exposures, aligning them, and then fusing them into a single HDR image, all while minimizing computational resources. Team CidautAI proposed the most efficient solution in terms of FLOPs and runtime. Their solution, named DarkIR-Fusion, addresses these constraints through a highly optimized method. The solution is based in the good results of DarkIR [24] in Low-Light Image Enhancement (LLIE).




Figure 7. General diagram of **DarkIR-Fusion** proposed by team CidautAI.

The architecture of their proposed model, **DarkIR-Fusion**, is presented in Figure 7. During the first stage, the set of nine input frames of different exposure times are passed through an Alignment stage. Then, in the second stage, the aligned images are introduced into the encoder-decoder DarkIR architecture, which finally returns a fused HDR image of the input set. The method is $10\times$ smaller than the requested size (30M), requires $14\times$ fewer operations than the hardware requirements, and runs in real time (≈ 15 FPS) on an NVIDIA H100 GPU — achieving almost 8 FPS on an RTX 4090.

Alignment stage. The nine input images are introduced and are grouped into the 3 trios of same exposition given in the dataset (see Figure 7). Each trio is introduced into the Alignment Module, and for each of the images the optical flow (flow) and mask are estimated using the FlowMask Block. This block applies cascaded convolutions to the concatenation of the reference and target images, returning the Mask and the Flow (see Figure 7).

DarkIR. The neural network follows an encoder-decoder architecture based on the Metaformer structure [96]. The encoder focuses on the HDR illumination and color issues using Fourier information. Thus, the encoder produces a low-resolution fused image $\hat{x}_{\downarrow 8}$ with corrected illumination and color. The team ensures that the encoder is working in these issues by the introduction of a guiding loss. The

decoder focuses on upscaling and reducing the misalignment blur and noise artifacts using the prior illumination-enhanced encoded features. The output of this DarkIR implementation is built upon a residual connection with the output of the Alignment Stage. This $[9,H,W]$ tensor is finally transformed into the output image using a convolutional 3×3 layer — which can be understood as a fusion-demaicing layer.

Training details. The proposed method was trained from scratch using only the challenge dataset. To train DarkIR-Fusion, the team used AdamW with setting $\beta_1 = 0.9$, $\beta_2 = 0.9$ and weight decay to 10^{-3} . The learning rate was initialized in 10^{-3} and was updated following a cosine annealing strategy [59] to a minimum 10^{-7} . Rectangular crops of varying sizes (scale 2:1) were used, with random horizontal and vertical flips applied. The training follows a multi-step strategy, reducing the batch size in each step, while making the crop size larger. Across four different consecutive steps for [1500, 500, 300, 20] epochs, they used patch sizes [(256,512), (384,768), (512,1024), (768,1536)] and batch sizes [32, 16, 8, 4], respectively. The model was trained on four H100 GPUs approximately 20 hours. The following combination of losses was used for optimization:

$$\mathcal{L} = \|x - \hat{x}\|^2 + 50 \cdot \|\nabla x - \nabla \hat{x}\|^2 + 0.8 \cdot \|x_{\downarrow 8} - \hat{x}_{\downarrow 8}\|_{YUV}. \quad (1)$$




Figure 8. Our proposed enhanced alignment and permuted self-attention for burst HDR and restoration.

All distances in (1) were calculated using the \mathcal{L}_1 norm. ∇ stands for gradient operation and YUV for the color space transformation. The reference ground-truth image and the cleaned image are, respectively, x and \hat{x} .

4.6. X-L

General method description. In the task of burst HDR and restoration, efficiently extracting information from multiple frames and performing high-performance multi-frame alignment, fusion, and reconstruction is crucial. To address this, team X-L proposed a method using a feature encoder that includes five Residual Channel Attention Blocks (RCABs) to extract key information [108]. These features are then fed into an enhanced deformable alignment module [60], which aligns neighboring frames to the reference frame. After the alignment module, the features are processed through a cascaded Permuted Self-Attention Blocks (PSABs) to model global relationships [112]. Finally, the features are fed to a decoder, which consists of five RCABs and one convolutional layer, to produce the final output. This approach ensures robust alignment and effective global context modeling.

Training strategy. During the training phase, they utilized the Adam optimizer with exponential decay rates set to $\beta_1 = 0.9$ and $\beta_2 = 0.999$. The initial learning rate was configured at 4×10^{-4} and was halved every 200 epochs. They utilized the Charbonnier penalty loss, and the batch size was set to 4. The proposed method was implemented using the PyTorch framework and executed on a single NVIDIA 4090 GPU.

5. Discussion and Conclusion

5.1. Discussion

Observing the diverse approaches of participants, it is first worth noting that almost all participants shared a common model structure, performing frame alignment first and then restoration. Indeed, as team ImvisionAI analyzed this competition in Section 4.1, the approach of dividing the roles of each module and solving the problem step by step, rather

than performing multiple tasks simultaneously with a single model, achieved effective results. Although there were small variations in how the optical flow was computed (e.g., Spynet[70] (team ImvisionAI), TMRnet[36] (team DeepTrans), U-net[74] (team SimonLarsen), simple deformable encoder[17] (team X-L), etc.), computing the optical flow to induce and influence warping took precedence over the restoration stage. Further note that, team SimonLarsen and team X-L tried multi-frame alignment on the extracted feature spaces. This approach would be significant to conduct additional studies to determine whether aligning over the denoised or extracted time-spatial features, as team X-L tried, could yield better results.

Secondly, most teams imposed a simple loss function, which is a common method in competitions to maximize the PSNR value. Team ImvisionAI used PSNR loss directly, while team DeepTrans and team SimonLarsen used the L^1 and L^2 loss functions, respectively. Team CidautAI further imposed an additional gradient-based loss (1), but it still shares a similar insight with the L^1 loss. If one needs to solve tasks where qualitative results are more important and increasing PSNR is not the top priority, using additional losses and regularizations such as score distillation [38, 66, 76, 83] may lead to improved results.

Thirdly, we discuss the efficiency of the submitted models. Although team ImvisionAI’s model records the best in performance, it also tightly consumes the competition’s resource constraints. The second-place team, DeepTrans, achieved even better results than SimonLarsen with fewer parameters. Although it consumed more FLOPs, it was measured to have a faster inference time when provided with a high-end GPU. If the environment requires a low-end GPU or NPU and inference time is more important, such as in a mobile smartphone, team SimonLarsen’s results may be more suitable. Lastly, team CidautAI focused on optimizing the model and achieved the minimum inference time. Their approach could be developed further by slightly increasing the model size (simply the number of layers and channels) to achieve better performance, sacrificing a little inference time.

5.2. Conclusion

This paper provides a comprehensive overview of the *NTIRE 2025 Efficient Burst HDR and Restoration* challenge and its results. Out of 217 registered participants, six teams submitted their final results. The competition introduced a novel Burst HDR fusion dataset consisting of 300 scenes, each with nine multi-exposure input frames. Team ImvisionAI emerged as the winner, achieving the highest PSNR value of 43.22 dB on this dataset. They introduced a recursive *Flow-based Enhanced Deformable Alignment* (F-EDA) module for handling multi-exposure images and adopted a two-stage training strategy to separately learn frame alignment and restoration tasks. The other five teams also proposed efficient models and learning strategies, each emphasizing different aspects of time and memory efficiency, which could benefit related tasks in the future.

Finally, we suggest that this competition could be further enhanced by considering additional metrics, such as both PSNR and runtime, or by introducing further degradations in image signal processing (e.g., bad pixel correction, fixed-pattern noise, lens shading correction, etc.).

Acknowledgments

This work was partially supported by the Humboldt Foundation. We thank the NTIRE 2025 sponsors: ByteDance, Meituan, Kuaishou, and University of Wurzburg (Computer Vision Lab).

A. Teams and affiliations

NTIRE 2025 team

Title:

NTIRE 2025 Efficient Burst HDR and Restoration Challenge

Members:

Sangmin Lee¹ (sangmin.lee@samsung.com), Eunpil Park¹, Hyunhee Park¹, Hyung-Ju Chun¹, Youngjo Kim¹, Angel Canelo¹, Chongyi Li², ChunLe Guo², Xin Jin², Radu Timofte³

Affiliations:

¹ Department of Camera Innovation Group, Samsung Electronics, South Korea

² College of Computer Science, Nankai University, China

³ Computer Vision Lab, University of Würzburg, Germany

ImvisionAI

Title:

Recursive Multi-Exposure Alignment with Spatiotemporal Decoupling for Efficient Burst HDR and Restoration

Members:

Qi Wu¹ (wuqiresearch@gmail.com), Tianheng Qiu²,

Yuchun Dong¹, Shenglin Ding¹, Guanghua Pan¹

Affiliations:

¹ Imvision

² University of Science and Technology of China, China

DeepTrans

Title:

Flow-Guided Deformable Alignment with Channel-wise Self-Attention Reconstruct for Efficient Burst HDR Restoration

Members:

Weiyu Zhou¹ (17355710941@163.com), Tao Hu¹, Yixu Feng¹, Duwei Dai², Yu Cao³, Peng Wu¹, Wei Dong⁴, Yanning Zhang¹, Qingsen Yan¹

Affiliations:

¹ School of Computer Science, Northwestern Polytechnical University, China

² Second Affiliated Hospital Of Xi'an Jiaotong University, China

³ Xi'an Institute of Optics and Precision Mechanics of CAS, China

⁴ Xi'an University of Architecture and Technology, China

SimonLarsen

Title:

Efficient Alignment and Fusion with Dense Flow Estimation and ConvNeXt Residual Dense Blocks

Members:

Simon J. Larsen¹ (sjl@esoft.com),

Affiliations:

¹ Esoft, Denmark

E_Group

Title:

A Hierarchical Fourier-based Transformer for Burst HDR and Restoration

Members:

Ruixuan Jiang¹ (rxjiang21@gmail.com), Senyan Xu¹, Xingbo Wang¹, Xin Lu¹

Affiliations:

¹ University of Science and Technology of China, China

CidautAI

Title:

Efficient Burst Aligning HDR Restoration based in FFT and Large Receptive Field Spatial Attention

Members:

Marcos V. Conde¹ (marcos.conde@uni-wuerzburg.de), Javier Abad-Hernández¹, Álvaro García-Lara¹, Daniel

Feijoo¹, Álvaro García¹

Affiliations:

¹ CidautAI

X-L

Title:

Burst HDR and Restoration via Enhanced Alignment and Permuted Self-Attention

Members:

Zeyu Xiao¹ (zeyuxiao1997@163.com), Zhuoyuan Li²

Affiliations:

¹ National University of Singapore, Singapore

² University of Science and Technology of China, China

References

- [1] Abdelrahman Abdelhamed, Mahmoud Afifi, Radu Timofte, and Michael S Brown. Ntire 2020 challenge on real image denoising: Dataset, methods and results. In *CVPR Workshops*, 2020. 1
- [2] Goutam Bhat, Martin Danelljan, and Radu Timofte. Ntire 2021 challenge on burst super-resolution: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 613–626, 2021. 2
- [3] Goutam Bhat, Martin Danelljan, Luc Van Gool, and Radu Timofte. Deep burst super-resolution. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9209–9218, 2021. 1, 2
- [4] Goutam Bhat, Martin Danelljan, Radu Timofte, Yizhen Cao, Yuntian Cao, Meiya Chen, Xihao Chen, Shen Cheng, Akshay Dudhane, Haoqiang Fan, et al. Ntire 2022 burst super-resolution challenge. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1041–1061, 2022. 2, 3
- [5] Goutam Bhat, Michaël Gharbi, Jiawen Chen, Luc Van Gool, and Zhihao Xia. Self-supervised burst super-resolution. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 10605–10614, 2023. 2
- [6] Tim Brooks, Ben Mildenhall, Tianfan Xue, Jiawen Chen, Dillon Sharlet, and Jonathan T Barron. Unprocessing images for learned raw denoising. In *CVPR*, 2019. 1
- [7] Genggeng Chen, Kexin Dai, Kangzhen Yang, Tao Hu, Xianguyu Chen, Yongqing Yang, Wei Dong, Peng Wu, Yanning Zhang, and Qingsen Yan. Bracketing image restoration and enhancement with high-low frequency decomposition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6097–6107, 2024. 1
- [8] Su-Kai Chen, Hung-Lin Yen, Yu-Lun Liu, Min-Hung Chen, Hou-Ning Hu, Wen-Hsiao Peng, and Yen-Yu Lin. Learning continuous exposure value representations for single-image hdr reconstruction. In *ICCV*, 2023. 1
- [9] Zheng Chen, Zongwei Wu, Eduard Zamfir, Kai Zhang, Yulun Zhang, Radu Timofte, Xiaokang Yang, Hongyuan Yu, Cheng Wan, Yuxin Hong, et al. Ntire 2024 challenge on image super-resolution (x4): Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6108–6132, 2024. 3
- [10] Zheng Chen, Kai Liu, Jue Gong, Jingkai Wang, Lei Sun, Zongwei Wu, Radu Timofte, Yulun Zhang, et al. NTIRE 2025 challenge on image super-resolution (x4): Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [11] Zheng Chen, Jingkai Wang, Kai Liu, Jue Gong, Lei Sun, Zongwei Wu, Radu Timofte, Yulun Zhang, et al. NTIRE 2025 challenge on real-world face restoration: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [12] Sung-Jin Cho, Seo-Won Ji, Jun-Pyo Hong, Seung-Won Jung, and Sung-Jea Ko. Rethinking coarse-to-fine approach in single image deblurring. In *ICCV*, 2021. 1
- [13] Xiaojie Chu, Liangyu Chen, Chengpeng Chen, and Xin Lu. Improving image restoration by revisiting global information aggregation. In *ECCV*, pages 53–71. Springer, 2022. 6, 7
- [14] Marcos Conde, Radu Timofte, et al. NTIRE 2025 challenge on raw image restoration and super-resolution. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [15] Marcos Conde, Radu Timofte, et al. Raw image reconstruction from RGB on smartphones. NTIRE 2025 challenge report. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [16] Marcos V Conde, Eduard Zamfir, Radu Timofte, Daniel Motilla, Cen Liu, Zexin Zhang, Yunbo Peng, Yue Lin, Jiaming Guo, Xueyi Zou, et al. Efficient deep models for real-time 4k image super-resolution. ntire 2023 benchmark and report. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1495–1521, 2023. 4
- [17] Jifeng Dai, Haozhi Qi, Yuwen Xiong, Yi Li, Guodong Zhang, Han Hu, and Yichen Wei. Deformable convolutional networks. In *Proceedings of the IEEE international conference on computer vision*, pages 764–773, 2017. 10
- [18] Xinwei Dai, Yuanbo Zhou, Xintao Qiu, Hui Tang, Wei Deng, Qinquan Gao, and Tong Tong. Learnable global spatio-temporal adaptive aggregation for bracketing image restoration and enhancement. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 6235–6245, 2024. 1
- [19] Michel Deudon, Alfredo Kalaitzis, Israel Goytom, Md Rifat Arefin, Zhichao Lin, Kris Sankaran, Vincent Michalski, Samira E Kahou, Julien Cornebise, and Yoshua Bengio. Highres-net: Recursive fusion for multi-frame super-resolution of satellite imagery. *arXiv preprint arXiv:2002.06460*, 2020. 1
- [20] Akshay Dudhane, Syed Waqas Zamir, Salman Khan, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Burst image

- restoration and enhancement. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5759–5768, 2022. 1, 2
- [21] Akshay Dudhane, Syed Waqas Zamir, Salman Khan, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Burstformer: Burst image restoration and enhancement transformer. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5703–5712. IEEE, 2023. 1, 2
- [22] Gabriel Eilertsen, Joel Kronander, Gyorgy Denes, Rafał K Mantiuk, and Jonas Unger. Hdr image reconstruction from a single exposure using deep cnns. *ACM TOG*, 2017. 1
- [23] Egor Ershov, Sergey Korchagin, Alexei Khalin, Artyom Panshin, Arseniy Terekhin, Ekaterina Zaychenkova, Georgiy Lobarev, Vsevolod Plohotnyuk, Denis Abramov, Elisey Zhdanov, Sofia Dorogova, Yasin Mamedov, Nikola Banic, Georgii Perevozchikov, Radu Timofte, et al. NTIRE 2025 challenge on night photography rendering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [24] Daniel Feijoo, Juan C Benito, Alvaro Garcia, and Marcos V Conde. Darkir: Robust low-light image restoration. *arXiv preprint arXiv:2412.13443*, 2024. 8
- [25] Yuqian Fu, Xingyu Qiu, Bin Ren Yanwei Fu, Radu Timofte, Nicu Sebe, Ming-Hsuan Yang, Luc Van Gool, et al. NTIRE 2025 challenge on cross-domain few-shot object detection: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [26] Clément Godard, Kevin Matzen, and Matt Uyttendaele. Deep burst denoising. In *Proceedings of the European conference on computer vision (ECCV)*, pages 538–554, 2018. 1
- [27] Shi Guo, Zifei Yan, Kai Zhang, Wangmeng Zuo, and Lei Zhang. Toward convolutional blind denoising of real photographs. In *CVPR*, 2019. 1
- [28] Shi Guo, Xi Yang, Jianqi Ma, Gaofeng Ren, and Lei Zhang. A differentiable two-stage alignment scheme for burst image reconstruction with large shift. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 17472–17481, 2022. 1
- [29] Shuhao Han, Haotian Fan, Fangyuan Kong, Wenjie Liao, Chunle Guo, Chongyi Li, Radu Timofte, et al. NTIRE 2025 challenge on text to image generation model quality assessment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [30] Samuel W Hasinoff, Dillon Sharlet, Ryan Geiss, Andrew Adams, Jonathan T Barron, Florian Kainz, Jiawen Chen, and Marc Levoy. Burst photography for high dynamic range and low-light imaging on mobile cameras. *ACM Transactions on Graphics (ToG)*, 35(6):1–12, 2016. 1
- [31] Chih-Chung Hsu, Chia-Ming Lee, and Yi-Shiuan Chou. Drcr: Saving image super-resolution away from information bottleneck. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6133–6142, 2024. 7
- [32] Quan Huynh-Thu and Mohammed Ghanbari. Scope of validity of psnr in image/video quality assessment. *Electronics letters*, 44(13):800–801, 2008. 3
- [33] Andrey Ignatov, Radu Timofte, Shuai Liu, Chaoyu Feng, Furui Bai, Xiaotao Wang, Lei Lei, Ziyao Yi, Yan Xiang, Zibin Liu, et al. Learned smartphone isp on mobile gpus with deep learning, mobile ai & aim 2022 challenge: report. In *European Conference on Computer Vision*, pages 44–70. Springer, 2022. 4
- [34] Varun Jain, Zongwei Wu, Quan Zou, Louis Florentin, Henrik Turbell, Sandeep Siddhartha, Radu Timofte, et al. NTIRE 2025 challenge on video quality enhancement for video conferencing: Datasets, methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [35] Xingyu Jiang, Xiuhui Zhang, Ning Gao, and Yue Deng. When fast fourier transform meets transformer for image restoration. In *Computer Vision – ECCV 2024*, pages 381–402, Cham, 2025. Springer Nature Switzerland. 8
- [36] Yueming Jin, Yonghao Long, Cheng Chen, Zixu Zhao, Qi Dou, and Pheng-Ann Heng. Temporal memory relation network for workflow recognition from surgical video. *IEEE Transactions on Medical Imaging*, 40(7):1911–1923, 2021. 10
- [37] EungGu Kang, Byeonghun Lee, Sunghoon Im, and Kyong Hwan Jin. Burstm: Deep burst multi-scale sr using fourier space with optical flow. In *European Conference on Computer Vision*, pages 459–477. Springer, 2024. 1, 2
- [38] Kwanyoung Kim, Taesung Kwon, and Jong Chul Ye. Noise distribution adaptive self-supervised image denoising using tweedie distribution and score matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2008–2016, 2022. 10
- [39] Bruno Lecouat, Thomas Eboli, Jean Ponce, and Julien Mairal. High dynamic range and super-resolution from raw image bursts. *arXiv preprint arXiv:2207.14671*, 2022. 1
- [40] Christian Ledig, Lucas Theis, Ferenc Huszár, Jose Caballero, Andrew Cunningham, Alejandro Acosta, Andrew Aitken, et al. Photo-realistic single image super-resolution using a generative adversarial network. In *CVPR*, 2017. 1
- [41] Siyeong Lee, Gwon Hwan An, and Suk-Ju Kang. Deep recursive hdri: Inverse tone mapping using generative adversarial networks. In *ECCV*, 2018. 1
- [42] Sangmin Lee, Eunpil Park, Angel Canelo, Hyunhee Park, Youngjo Kim, Hyungju Chun, Xin Jin, Chongyi Li, Chunle Guo, Radu Timofte, et al. NTIRE 2025 challenge on efficient burst hdr and restoration: Datasets, methods, and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [43] Dasong Li, Yi Zhang, Ka Lung Law, Xiaogang Wang, Hongwei Qin, and Hongsheng Li. Efficient burst raw denoising with variance stabilization and multi-frequency denoising network. *International Journal of Computer Vision*, 130(8):2060–2080, 2022. 1
- [44] Xin Li, Yeying Jin, Xin Jin, Zongwei Wu, Bingchen Li, Yufei Wang, Wenhan Yang, Yu Li, Zhibo Chen, Bihan Wen,

- Robby Tan, Radu Timofte, et al. NTIRE 2025 challenge on day and night raindrop removal for dual-focused images: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [45] Xin Li, Xijun Wang, Bingchen Li, Kun Yuan, Yizhen Shao, Suhang Yao, Ming Sun, Chao Zhou, Radu Timofte, and Zhibo Chen. NTIRE 2025 challenge on short-form ugc video quality assessment and enhancement: Kwaisr dataset and study. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [46] Xin Li, Kun Yuan, Bingchen Li, Fengbin Guan, Yizhen Shao, Zihao Yu, Xijun Wang, Yiting Lu, Wei Luo, Suhang Yao, Ming Sun, Chao Zhou, Zhibo Chen, Radu Timofte, et al. NTIRE 2025 challenge on short-form ugc video quality assessment and enhancement: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [47] Yawei Li, Yulun Zhang, Radu Timofte, Luc Van Gool, Zhi-jun Tu, Kunpeng Du, Hailing Wang, Hanting Chen, Wei Li, Xiaofei Wang, et al. Ntire 2023 challenge on image denoising: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1905–1921, 2023. 1, 3
- [48] Jingyun Liang, Jie Zhang Cao, Guolei Sun, Kai Zhang, Luc Van Gool, and Radu Timofte. Swinir: Image restoration using swin transformer. In *ICCV*, 2021. 1
- [49] Jie Liang, Radu Timofte, Qiaosi Yi, Zhengqiang Zhang, Shuaizheng Liu, Lingchen Sun, Rongyuan Wu, Xindong Zhang, Hui Zeng, Lei Zhang, et al. NTIRE 2025 the 2nd restore any image model (RAIM) in the wild challenge. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [50] Bee Lim, Sanghyun Son, Heewon Kim, Seungjun Nah, and Kyoung Mu Lee. Enhanced deep residual networks for single image super-resolution. In *CVPR Workshops*, 2017. 1
- [51] Jingbo Lin, Zhilu Zhang, Yuxiang Wei, Dongwei Ren, Dongsheng Jiang, and Wangmeng Zuo. Improving image restoration through removing degradations in textual representations. *arXiv preprint arXiv:2312.17334*, 2023. 1
- [52] Wenjie Lin, Zhen Liu, Chengzhi Jiang, Mingyan Han, Ting Jiang, and Shuaicheng Liu. Improving bracket image restoration and enhancement with flow-guided alignment and enhanced feature aggregation. *arXiv preprint arXiv:2404.10358*, 2024. 1
- [53] Jiaming Liu, Chi-Hao Wu, Yuzhi Wang, Qin Xu, Yuqian Zhou, Haibin Huang, Chuan Wang, Shaofan Cai, Yifan Ding, Haoqiang Fan, et al. Learning raw image denoising with bayer pattern unification and bayer preserving augmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pages 0–0, 2019. 6, 7
- [54] Ming Liu, Zhilu Zhang, Liya Hou, Wangmeng Zuo, and Lei Zhang. Deep adaptive inference networks for single image super-resolution. In *ECCV Workshops*, 2020. 1
- [55] Xiaohong Liu, Xiongkuo Min, Qiang Hu, Xiaoyun Zhang, Jie Guo, et al. NTIRE 2025 XGC quality assessment challenge: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [56] Xiaoning Liu, Zongwei Wu, Florin-Alexandru Vasluianu, Hailong Yan, Bin Ren, Yulun Zhang, Shuhang Gu, Le Zhang, Ce Zhu, Radu Timofte, et al. NTIRE 2025 challenge on low light image enhancement: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [57] Yu-Lun Liu, Wei-Sheng Lai, Yu-Sheng Chen, Yi-Lung Kao, Ming-Hsuan Yang, Yung-Yu Chuang, and Jia-Bin Huang. Single-image hdr reconstruction by learning to reverse the camera pipeline. In *CVPR*, 2020. 1
- [58] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11976–11986, 2022. 7
- [59] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2022. 6, 8, 9
- [60] Ziwei Luo, Lei Yu, Xuan Mo, Youwei Li, Lanpeng Jia, Haoqiang Fan, Jian Sun, and Shuaicheng Liu. Ebsr: Feature enhanced burst super-resolution with deformable alignment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 471–478, 2021. 10
- [61] Ziwei Luo, Youwei Li, Shen Cheng, Lei Yu, Qi Wu, Zhihong Wen, Haoqiang Fan, Jian Sun, and Shuaicheng Liu. Bsr: Improving burst super-resolution with swin transformer and flow-guided deformable alignment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 998–1008, 2022. 2
- [62] Xintian Mao, Yiming Liu, Fengze Liu, Qingli Li, Wei Shen, and Yan Wang. Intriguing findings of frequency selection for image deblurring. In *AAAI*, 2023. 1
- [63] Ben Mildenhall, Jonathan T Barron, Jiawen Chen, Dillon Sharlet, Ren Ng, and Robert Carroll. Burst denoising with kernel prediction networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2502–2510, 2018. 1
- [64] Antoine Monod, Julie Delon, and Thomas Veit. An analysis and implementation of the hdr+ burst denoising method. *Image Processing On Line*, 11:142–169, 2021. 1
- [65] Seungjun Nah, Tae Hyun Kim, and Kyoung Mu Lee. Deep multi-scale convolutional neural network for dynamic scene deblurring. In *CVPR*, 2017. 1
- [66] Thuan Hoang Nguyen and Anh Tran. Swiftbrush: One-step text-to-image diffusion model with variational score distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7807–7816, 2024. 10
- [67] Naama Pearl, Tali Treibitz, and Simon Korman. Nan: Noise-aware nerfs for burst-denoising. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12672–12681, 2022. 2
- [68] Eduardo Pérez-Pellitero, Sibi Catley-Chandar, Ales Leonardis, and Radu Timofte. Ntire 2021 challenge on

- high dynamic range imaging: Dataset, methods and results. In *CVPR Workshops*, 2021. 1
- [69] Tianheng Qiu, Qi Wu, Yuchun Dong, Shenglin Ding, Guanghua Pan, Xuan Huang, and Hu Wei. Recursive multi-exposure alignment with spatiotemporal decoupling for efficient burst hdr and restoration. In *CVPR Workshops*, 2025. 5
- [70] Anurag Ranjan and Michael J Black. Optical flow estimation using a spatial pyramid network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4161–4170, 2017. 5, 6, 10
- [71] Bin Ren, Yawei Li, Nancy Mehta, Radu Timofte, Hongyuan Yu, Cheng Wan, Yuxin Hong, Bingnan Han, Zhuoyuan Wu, Yajun Zou, et al. The ninth ntire 2024 efficient super-resolution challenge report. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6595–6631, 2024. 3
- [72] Bin Ren, Hang Guo, Lei Sun, Zongwei Wu, Radu Timofte, Yawei Li, et al. The tenth NTIRE 2025 efficient super-resolution challenge report. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [73] Xuejian Rong, Denis Demandolx, Kevin Matzen, Priyam Chatterjee, and Yingli Tian. Burst denoising via temporally shifted wavelet transforms. In *Computer Vision—ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XIII 16*, pages 240–256. Springer, 2020. 1
- [74] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical image computing and computer-assisted intervention—MICCAI 2015: 18th international conference, Munich, Germany, October 5-9, 2015, proceedings, part III 18*, pages 234–241. Springer, 2015. 7, 10
- [75] Nickolay Safonov, Alexey Bryntsev, Andrey Moskalenko, Dmitry Kulikov, Dmitriy Vatolin, Radu Timofte, et al. NTIRE 2025 challenge on UGC video enhancement: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [76] Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in neural information processing systems*, 32, 2019. 10
- [77] Lei Sun, Andrea Alfano, Peiqi Duan, Shaolin Su, Kaiwei Wang, Boxin Shi, Radu Timofte, Danda Pani Paudel, Luc Van Gool, et al. NTIRE 2025 challenge on event-based image deblurring: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [78] Lei Sun, Hang Guo, Bin Ren, Luc Van Gool, Radu Timofte, Yawei Li, et al. The tenth ntire 2025 image denoising challenge report. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [79] Thomas Tanay, Aleš Leonardis, and Matteo Maggioni. Efficient view synthesis and 3d-based multi-frame denoising with multiplane feature representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 20898–20907, 2023. 2
- [80] Xin Tao, Hongyun Gao, Xiaoyong Shen, Jue Wang, and Ji-aya Jia. Scale-recurrent network for deep image deblurring. In *CVPR*, 2018. 1
- [81] Florin-Alexandru Vasluiianu, Tim Seizinger, Zhuyun Zhou, Cailian Chen, Zongwei Wu, Radu Timofte, et al. NTIRE 2025 image shadow removal challenge report. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [82] Florin-Alexandru Vasluiianu, Tim Seizinger, Zhuyun Zhou, Zongwei Wu, Radu Timofte, et al. NTIRE 2025 ambient lighting normalization challenge. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [83] Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural computation*, 23(7):1661–1674, 2011. 10
- [84] Longguang Wang, Yulan Guo, Yingqian Wang, Juncheng Li, Shuhang Gu, Radu Timofte, Ming Cheng, Haoyu Ma, Qiufang Ma, Xiaopeng Sun, et al. Ntire 2023 challenge on stereo image super-resolution: Methods and results. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1346–1372, 2023. 3
- [85] Yingqian Wang, Longguang Wang, Zhengyu Liang, Jungang Yang, Radu Timofte, Yulan Guo, Kai Jin, Zeqiang Wei, Angulia Yang, Sha Guo, et al. Ntire 2023 challenge on light field image super-resolution: Dataset, methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1320–1335, 2023.
- [86] Yingqian Wang, Zhengyu Liang, Qianyu Chen, Longguang Wang, Jungang Yang, Radu Timofte, Yulan Guo, Wentao Chao, Yiming Kan, Xuechun Wang, et al. Ntire 2024 challenge on light field image super-resolution: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6218–6234, 2024. 3
- [87] Yingqian Wang, Zhengyu Liang, Fengyuan Zhang, Lvli Tian, Longguang Wang, Juncheng Li, Jungang Yang, Radu Timofte, Yulan Guo, et al. NTIRE 2025 challenge on light field image super-resolution: Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [88] Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004. 3
- [89] Pengxu Wei, Yujing Sun, Xingbei Guo, Chang Liu, Guanbin Li, Jie Chen, Xiangyang Ji, and Liang Lin. Towards real-world burst image super-resolution: Benchmark and method. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 13233–13242, 2023. 1, 2
- [90] Sanghyun Woo, Shoubhik Debnath, Ronghang Hu, Xinlei Chen, Zhuang Liu, In So Kweon, and Saining Xie. Convnext v2: Co-designing and scaling convnets with masked

- autoencoders. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 16133–16142, 2023. 7
- [91] Bartłomiej Wronski, Ignacio Garcia-Dorado, Manfred Ernst, Damien Kelly, Michael Krainin, Chia-Kai Liang, Marc Levoy, and Peyman Milanfar. Handheld multi-frame super-resolution. *ACM Transactions on Graphics (ToG)*, 38(4):1–18, 2019. 1
- [92] Zhihao Xia, Federico Perazzi, Michaël Gharbi, Kalyan Sunkavalli, and Ayan Chakrabarti. Basis prediction networks for effective burst denoising with large kernels. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11844–11853, 2020. 1
- [93] Xiaoxia Xing, Hyunhee Park, Fan Wang, Ying Zhang, Sejun Song, Changho Kim, and Xiangyu Kong. High quality reference feature for two stage bracketing image restoration and enhancement. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6267–6276, 2024. 1
- [94] Kangzhen Yang, Tao Hu, Kexin Dai, Genggeng Chen, Yu Cao, Wei Dong, Peng Wu, Yanning Zhang, and Qingsen Yan. Crnet: A detail-preserving network for unified image restoration and enhancement task. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6086–6096, 2024. 1
- [95] Kangning Yang, Jie Cai, Ling Ouyang, Florin-Alexandru Vasluianu, Radu Timofte, Jiaming Ding, Huiming Sun, Lan Fu, Jinlong Li, Chiu Man Ho, Zibo Meng, et al. NTIRE 2025 challenge on single image reflection removal in the wild: Datasets, methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [96] Weihao Yu, Mi Luo, Pan Zhou, Chenyang Si, Yichen Zhou, Xinchao Wang, Jiashi Feng, and Shuicheng Yan. Metaformer is actually what you need for vision. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10819–10829, 2022. 9
- [97] Pierluigi Zama Ramirez, Fabio Tosi, Luigi Di Stefano, Radu Timofte, Alex Costanzino, Matteo Poggi, Samuele Salti, Stefano Mattoccia, et al. NTIRE 2025 challenge on hr depth from images of specular and transparent surfaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, 2025. 2
- [98] Eduard Zamfir, Zongwei Wu, Nancy Mehta, Yulun Zhang, and Radu Timofte. See more details: Efficient image super-resolution by experts mining. In *Forty-first International Conference on Machine Learning*, 2024. 3
- [99] Syed Waqas Zamir, Aditya Arora, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, Ming-Hsuan Yang, and Ling Shao. Cycleisp: Real image restoration via improved data synthesis. In *CVPR*, 2020. 1
- [100] Syed Waqas Zamir, Aditya Arora, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, Ming-Hsuan Yang, and Ling Shao. Multi-stage progressive image restoration. In *CVPR*, 2021. 1
- [101] Syed Waqas Zamir, Aditya Arora, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Restormer: Efficient transformer for high-resolution image restoration. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5728–5739, 2022. 6
- [102] Matthew D Zeiler, Graham W Taylor, and Rob Fergus. Adaptive deconvolutional networks for mid and high level feature learning. In *2011 international conference on computer vision*, pages 2018–2025. IEEE, 2011. 6
- [103] Jiawei Zhang, Jinshan Pan, Jimmy Ren, Yibing Song, Linchao Bao, Rynson WH Lau, and Ming-Hsuan Yang. Dynamic scene deblurring using spatially variant recurrent neural networks. In *CVPR*, 2018. 1
- [104] Kai Zhang, Wangmeng Zuo, Yunjin Chen, Deyu Meng, and Lei Zhang. Beyond a gaussian denoiser: Residual learning of deep cnn for image denoising. *IEEE TIP*, 2017. 1
- [105] Kai Zhang, Wangmeng Zuo, and Lei Zhang. Ffdnet: Toward a fast and flexible solution for cnn-based image denoising. *IEEE TIP*, 2018. 1
- [106] Kai Zhang, Wangmeng Zuo, and Lei Zhang. Learning a single convolutional super-resolution network for multiple degradations. In *CVPR*, 2018. 1
- [107] Yulun Zhang, Kunpeng Li, Kai Li, Lichen Wang, Bineng Zhong, and Yun Fu. Image super-resolution using very deep residual channel attention networks. In *ECCV*, 2018. 1
- [108] Yulun Zhang, Kunpeng Li, Kai Li, Lichen Wang, Bineng Zhong, and Yun Fu. Image super-resolution using very deep residual channel attention networks. In *Proceedings of the European conference on computer vision (ECCV)*, pages 286–301, 2018. 10
- [109] Yulun Zhang, Kai Zhang, Zheng Chen, Yawei Li, Radu Timofte, Junpei Zhang, Kexin Zhang, Rui Peng, Yanbiao Ma, Licheng Jia, et al. Ntire 2023 challenge on image super-resolution (x4): Methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1865–1884, 2023. 3
- [110] Zhilu Zhang, Shuohao Zhang, Renlong Wu, Zifei Yan, and Wangmeng Zuo. Exposure bracketing is all you need for unifying image restoration and enhancement tasks. *arXiv preprint arXiv:2401.00766*, 2024. 1
- [111] Zhilu Zhang, Shuohao Zhang, Renlong Wu, Wangmeng Zuo, Radu Timofte, Xiaoxia Xing, Hyunhee Park, Sejun Song, Changho Kim, Xiangyu Kong, et al. Ntire 2024 challenge on bracketing image restoration and enhancement: Datasets methods and results. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6153–6166, 2024. 1, 2, 3
- [112] Yupeng Zhou, Zhen Li, Chun-Le Guo, Song Bai, Ming-Ming Cheng, and Qibin Hou. Srformer: Permuted self-attention for single image super-resolution. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12780–12791, 2023. 10
- [113] Yunhao Zou, Chenggang Yan, and Ying Fu. Rawhdr: High dynamic range image reconstruction from a single raw image. In *ICCV*, 2023. 1