



DATA SHEET NO. 7100-542

MEL-PRIME™

Solvent-Based VOC Adhesive

DESCRIPTION

MEL-PRIME is a solvent-based, ready-to-use adhesive for W. R. MEADOWS membrane systems. It is red to reddish-brown in color.

USES

MEL-PRIME simultaneously prepares and dustproofs new and old and vertical and horizontal surfaces in one easy, economical operation. MEL-PRIME is designed for surfaces to receive waterproofing and air/vapour barrier systems from W. R. MEADOWS. Use MEL-PRIME on surfaces to receive applications of MEL-ROL®, PRECON®, MEL-DEK™, and/or AIR-SHIELD™ from W. R. MEADOWS.

FEATURES/BENEFITS

- High solids for optimum performance.
- Ready-to-use ... no mixing or dilution required.
- For exterior vertical and horizontal applications.

PACKAGING

3.78 L (1 U.S. Gallon) Can
18.9 L (5 U.S. Gallon) Pail

COVERAGE

6.14 - 7.37 m²/L (250 - 300 ft.²/U.S. gallon)

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

APPLICATION

Surface Preparation ... All surfaces to receive adhesive must be clean, dry, smooth, and free of all voids. Fill all voids and remove sharp protrusions. When used on concrete, concrete should be cured at least 72 hours. For additional substrate surface preparation requirements, see instructions for applying MEL-ROL, PRECON, MEL-DEK, and/or AIR-SHIELD.

NOTE: Metal surfaces must also be clean, dry, and free of loose paint, rust, or other contaminants.

Application Method ... Apply MEL-PRIME with a roller or brush at a coverage rate of 6.14 - 7.37 m²/L (250 - 300 ft.²/gal.) Apply only to the area to be covered with the membrane during the working day. Areas not covered with a membrane in 24 hours must be re-applied. MEL-PRIME should be used at temperatures of -12° C and above for maximum adhesion. Protect the adhesive from dust, dirt, or any other contaminants that will cause a decrease in adhesion.

Drying Time ... Refer to dry time chart below for guidance. Temperatures above 35 °C will only result in a nominal decrease in dry time. The dry time for adhesives is defined as the point at which the surface becomes sticky/tacky.

Cleanup ... MEL-PRIME may be cleaned with mineral spirits.

LIMITATIONS/PRECAUTIONS

Do not apply MEL-PRIME when rain is imminent, or on damp or frost-covered surfaces. Avoid allowing MEL-PRIME to puddle – this will lengthen drying time. Do not dilute; use as is.

HEALTH HAZARDS

This product is flammable. Ignition sources should be removed prior to product use. Avoid direct contact with the product. Direct contact may cause mild to moderate irritation of the eyes and skin. Product vapours may also cause transient central nervous system depression. Refer to Safety Data Sheet for complete health and safety information.

MASTERFORMAT NUMBER AND TITLE

07 13 26 - Self-Adhering Sheet Waterproofing


For most recent data sheet, sustainability information, and SDS, visit www.wrmeadows.com.

2025-11-17

W. R. MEADOWS® OF CANADA
70 Hannant Court, Milton, ON L9T 5C1
21 Streambank Ave., Sherwood Park, AB T8H 1N1
(800) 342-5976
Montreal Sales: (514) 865-2406

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON
Sherwood Park, AB

www.wrmeadows.com
info@wrmeadows.com



® SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.