



DATA SHEET 7100-562

POINTING MASTIC

Cold-Applied, Single-Component Polymeric Sealing Compound

DESCRIPTION

POINTING MASTIC is a pre-mixed, cold-applied, polymeric, single-component sealing compound. POINTING MASTIC was specifically designed to seal all exterior, vertical, and horizontal terminations of MEL-ROL®, PRECON®, MEL-DEK™, AIR-SHIELD™, PERMINATOR®, and PREMOULDED MEMBRANE® VAPOR SEAL WITH PLASMATIC® CORE from W. R. MEADOWS. It is also used for adhesive bonding of PROTECTION COURSE and MEL-DRAIN™. POINTING MASTIC can be used on all patches and overlaps in detail areas. It offers excellent cohesive and adhesive qualities when applied to structural concrete, masonry, and/or wood. Once applied, it provides excellent adhesive and bonding strengths. POINTING MASTIC cures to form a tough, flexible membrane

USES

POINTING MASTIC is designed to meet a variety of building/construction product applications. These uses include sealing terminations for vertical or horizontal vapourproofing or waterproofing membranes, deck waterproofing systems, air barriers, and flashing membranes.

It is used for adhesive bonding of protection course boards and rolled matrix draining systems. POINTING MASTIC is also applied between membrane and clamping rings at all terminations, drains, and protrusions. In addition, POINTING MASTIC is ideal for sealing joints and concrete curbs and gutters. The product can also be used with sewer joints.

POINTING MASTIC can be applied to seal top edge horizontal terminations as well as the inside and outside corners of overlapping detail strips.

FEATURES/BENEFITS

- Premixed and easy to apply with caulking gun or trowel.
- Excellent cohesive and adhesive strengths.
- Will not lose bond once applied.
- Specifically developed for use with detail strips, vapourproofing and waterproofing membranes, protection course boards, and rolled matrix drainage systems

W. R. MEADOWS OF CANADA

70 Hannant Court, Milton, ON L9T 5C1
Phone: (905) 878-4122 • Fax: (905) 878-4125

Montreal Sales: (877) 405-5186

PACKAGING

857.65 mL (29 Oz.) Cartridges
18.93 L (5 Gal.) Pails

COVERAGE

Approximately 61 metres (200 lineal feet) per 3.79 litres (1 gallon), when used as directed.

SHELF LIFE

When stored indoors and in original, unopened containers at temperatures between 4 - 32° C (40 - 90° F), shelf life is a minimum of two years from date of manufacture.

APPLICATION

Surface Preparation ... All surfaces to receive an application of POINTING MASTIC should be dry, frost-free, clean, and free of all contaminants.

Application Method ... For easy application, store at temperatures of 16° C (60° F) or higher before using. Material will be stiffer and more difficult to work with at cooler temperatures. POINTING MASTIC can be easily applied with a caulking gun or trowel. Apply only in areas that will not be covered with a waterproofing membrane. Apply and spread the material to a thickness of approximately 3.18 mm (1/8") in a strip 25.4 - 76.2 mm (1" - 3") wide.

A bead of POINTING MASTIC is applied to the top edge horizontal termination of the vapourproofing or waterproofing membranes on vertical walls.

The corner and footing on inside corners are finished with POINTING MASTIC in the centre of the detail strip where the vertical wall and footing meet. The outside corner is finished with POINTING MASTIC in the lower centre point where vertical wall and footing meet.

POINTING MASTIC should also be applied at the laps around corners, extending 305 mm (12") in each direction from the corner.

Continued Over ...

Hampshire, IL/Cartersville, GA/York, PA/Fort Worth, TX
Benicia, CA/Pomona, CA/Goodyear, AZ/Milton, ON
St. Albert, AB

www.wrmeadows.com

A bead of POINTING MASTIC should also be applied between membrane and clamping rings and at all terminations, drains, and protrusions.

Cleanup ... Tools can be cleaned with mineral spirits at the end of each workday. Follow manufacturer's precautions when using a solvent as a cleaner.

PRECAUTIONS

POINTING MASTIC VAPOUR IS FLAMMABLE. Read and follow application information and Health and Safety information on product label.

MASTERFORMAT NUMBER AND TITLE

07 13 53 - Elastomeric Sheet Waterproofing

LEED INFORMATION

May help contribute to LEED credits:

- IEQ Credit 3.1: Construction Indoor Air Quality Management Plan: During Construction
- IEQ Credit 4.2: Low-Emitting Materials – Paints and Coatings
- IEQ Credit 7.1: Thermal Comfort – Design
- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

For most recent data sheet, further LEED information, and MSDS, visit www.wrmeadows.com.



2012-10-04

® SEALTIGHT is a registered trade mark of W. R. Meadows

WARRANTY: W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.