



## DATA SHEET NO. 4650-000

### KOOL-ROD™ Backer Rod for Cold-Applied Sealants

#### DESCRIPTION

KOOL-ROD is a closed cell, polyethylene, flexible, rope-like foam joint backing material.

This material is virtually non-absorbent and chemically inert to most solvents. KOOL-ROD will not stain or adhere to sealant materials. It is fully compatible with acrylic, butyl, polyurethane, polysulfide, silicone, and most other cold-applied sealant compounds.

KOOL-ROD is specifically designed as a compressible backing material to be used in conjunction with a wide variety of cold-applied joint sealants.

#### USES

KOOL-ROD is highly adaptable for both vertical and horizontal applications. It is commonly used in glazing operations, copings, between precast panels, and around door and window perimeters. It provides the perfect backing for all types of construction, expansion, isolation, control, and pavement joints.

#### FEATURES/BENEFITS

- Controls depth of sealant/Ensures proper joint design ratio.
- Forces sealant against joint sidewalls/Provides maximum sidewall adhesion.
- Sealants will not adhere to KOOL-ROD/Eliminates three-sided joint adhesion failure.
- Closed-cell foam technology/Does not allow air or moisture entrapment.
- Easily compressible, lightweight/Installs quickly, stays in place.
- Easy to handle, smaller packaging/Added contractor convenience.

#### PACKAGING

Diameter	Joint Width	Meters/Carton
6.35 mm (1/4")	4 mm (3/16")	1219 m (4000 LF)
9.53 mm ( <sup>3</sup> / <sub>8</sub> ")	6 mm (1/4")	640 m (2100 LF)
12.7 mm (1/2")	9 mm (3/8")	(777 m) 2550 LF
15.86 mm ( <sup>5</sup> / <sub>8</sub> ")	12 mm (1/2")	472 m (1550 LF)
19.05 mm (3/4")	15 mm (5/8")	335 m (1100 LF)
22 mm ( <sup>7</sup> / <sub>8</sub> ")	18 mm (11/16")	259 m (850 LF)
25 mm (1")	19 mm (3/4")	183 m (600 LF)
31 mm (1 <sup>1</sup> / <sub>4</sub> ")	22 mm (7/8")	122 m (400 LF)
38.1 mm (1 <sup>1</sup> / <sub>2</sub> ")	29 mm (1 1/8")	128 m (420 LF)
50.8 mm (2")	41 mm (1 5/8")	77 m (252 LF)
25.4 mm (2.5")	60 mm (2 1/8")	49 m (162 LM)
76.2 mm (3")	64 mm (2 1/2")	31 m (102 LF)
101.6 mm (4")	76 mm (3")	16.5 m (54 LF)

Continued over ...

**W. R. MEADOWS® OF CANADA**  
70 Hannant Court, Milton, ON L9T 5C1  
21 Streambank Ave., Sherwood Park, AB T8H 1N1  
(800) 342-5976  
Montreal Sales: (514) 865-2406

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON  
Sherwood Park, AB  
[www.wrmeadows.com](http://www.wrmeadows.com)  
[info@wrmeadows.com](mailto:info@wrmeadows.com)



## BAG PACKAGING

Diameter	Joint Width	Meters/Carton
6.35 mm (1/4")	4 mm (3/16")	152.4 m (500')
9.53 mm (3/8")	6 mm (1/4")	70.1 m (230')
12.7 mm (1/2")	9 mm (3/8")	39.6 m (130')
15.86 mm (5/8")	12 mm (1/2")	22.86 m (75')
19.05 mm (3/4")	15 mm (5/8")	16.76 m (55')

Color: Dark Gray

## SPECIFICATIONS

- ASTM C1330, Type B
- ASTM D5249, Type 3

## APPLICATION

Joint or opening must be clean, dry, and free of obstructions. Select the proper rod diameter and cut to length or use directly from the spool. With a blunt instrument or roller, uniformly install rod at a level recommended by the sealant manufacturer, specifier, or architect. Generally, the depth of the joint after KOOL-ROD is installed should be half the width. Very large and very small joints vary in terms of this depth-to-width ratio.

Do not tear, puncture, twist, or overly compress the backer rod during installation. Caution should be used to avoid any situation where voids may form and trap air/moisture between backer rod and sealant. Care should also be taken to prevent the introduction of air bubbles into the sealant during mixing (if any) and/or installation.

## MASTERFORMAT NUMBER AND TITLE

07 91 23 - Backer Rods

2025-06-05

® SEALTIGHT is a registered trade mark of W. R. Meadows

**WARRANTY:** W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.